

UHW-10/20 FHW-10

HEADSETS WIRELESS



No wires, no plugs, just crystal clear, mission-critical communication with Firecom's new wireless headset and base station. The wireless headset

No Plug Just Play.

connects first responders to the in-cab intercom system, at the pump panel or within 90 feet of the base station.

The headset is ideal for command vehicles, on scene first responders and ambulance attendants.

The wireless headset has two base station configurations. The one channel model uses one radio transmit headset. The five channel model works with up to five non-radio transmit headsets. The system allows up to 40 wireless headsets with any combination of base stations in close vicinity to each other.



UHW-10/20 Headset

Single Headset Base Station

UHW-10/20 FHW-10
HEADSETS WIRELESS



www.firecom.com

Single Headset Base Station

The single headset base station accommodates a single UHW/FHW series radio transmit wireless headset. The base station can be connected via a 6 conductor flat RJ-6 cable to any headset port on Firecom's 30XXR series intercom. The base station will provide full duplex audio and PTT communication between the wireless headset and the intercom.

Multiple Headset Base Station

The multiple headset base station accommodates up to five UHW/FHW series non-radio transmit wireless headsets. The base station can be connected via a 6 conductor flat RJ-6 cable to any headset port on Firecom's 30XXR series intercoms. The base station will provide full duplex audio communication between the wireless headset and the intercom. Any combination of up to 40 radio-transmit and non radio-transmit headsets connected to single and multiple headset bases can operate simultaneously, in close proximity to each other, for interference free communications.

Firecom's wireless headset enhances communication and delivers vital hearing protection. Firecom's protective design reduces ambient noise and meets NFPA 1500 standards.

Easy to use, efficient, durable and now wireless.

FHW-10 Headsets and Multiple Headset Base Station



Warranty

All Firecom products are protected with a two-year limited warranty.

© 2007, A Division of Sonetics Corporation.
Specifications subject to change without notice.

Specifications

Headsets

Sensitivity	104dB re 20uPa @ 1000 Hz, 1 mW
Frequency Response	300Hz - 3.4 KHz, +/- 3dB
Impedance	32 ohms nominal
Weight (UHW-10/20)	17.80z
Weight (FHW-10)	19.50z

Microphone

Frequency Response	Optimized for speech clarity and noise reduction
Max. Amb. Noise Level	125dB SPL re 20uPa
MIC Sensitivity	-44 +/- 5db, 0dB=1v/Pa
DC Bias	Internally Biased
Frequency range	300Hz - 3.4KHz
Noise Canceling	approx. 6.25 db/octave from 3.4 KHz down to 300 Hz
S/N ratio	60db minimum
Impedance	Internally matched

RF

- Range: 300' open field, 90' minimum from base station mounted on fire or emergency truck.
- Digital encoding for secured communications
- Interference free communications for up to 40 headsets operating in close proximity.
- Immunity to interference from other communications devices operating in the entire frequency spectrum from 30 MHz-18 GHz.

FCC Compliance

Pending FCC approval, this device complies with FCC Rules Part 15. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference that may be received, including interference that may cause undesired operation.

Power

- 3.7V rechargeable lithium Ion battery
- 8-10 hours of talk time
- Cycle life 500 cycles minimum
- Over voltage, under voltage, over current and over temperature protection
- Charge source 12V nominal (11-18v). 0.25A minimum
- Charge time 3 hours maximum from deeply discharged state

Environmental:

- Operating temperature -10 to+70°C
- Storage temperature -25 to+85°C
- Meets standards SAE J1455 and J1113
- Chemical resistance corrosion and humidity per MIL-STD-810

Base Station Specifications

Electrical:

- Power: Nominal 12V (11-16V)
- Current draw: 45mA average, 80mA peak
- Reverse voltage protection
- Immune to ESD and transients per SAE standard J1113
- EMC compatible per standard J1113

Mechanical:

- Dimensions: 5.7"L x 2.6"W x 1.14"H
- Weight: 4.24 Oz (0.265Lb)

7340 SW Durham Road • Portland, OR 97224 USA
1-800-527-0555 • Phone: 503-684-6647
Fax: 503-620-2943 • email: sales@firecom.com



www.firecom.com